


LED SOLARIS

4500 lm / 50 W
NEXTGEN




50 W
total power


6°
spot angle


4500 lm
light output

The regular umbilical light kit contains*:

- charger
- hex keys
- chosen battery
- chosen headlamp
- spare plug o-rings
- plastic carrying case
- HD connecting cable

*the contents of the kit can be freely modified during the ordering



for more check our webside

OPERATING TIME* LED SOLARIS NEXTGEN kits



LED SOLARIS NEXTGEN
+ ACCU TYPE 10

3h 20'



LED SOLARIS NEXTGEN
+ ACCU TYPE 14

4h 35'



LED SOLARIS NEXTGEN
+ ACCU TYPE 24

8h

*measured at OPERATIONAL MODE (60% of light intensity)

ACCESORIES



HEAVY DUTY CABLE



90° SIDEMOUNT
CONNECTING CABLE



CLICK MOUNT



MODULAR GOODMAN
HANDLE



GOODMAN HANDLE
STANDARD



GOODMAN HANDLE
SOFT

SPECIFICATION

| | |
|--------------------|-------------------------------|
| light output | 4500 lm |
| spot angle | 6° |
| corona | noticeable corona effect |
| type of optics | 5 x LED reflector |
| total power | 50 W |
| light source | 5 x XPL HI LED CREE® |
| colour temperature | cool white |
| power source | external rechargeable battery |

| | |
|---------------------|--|
| material | hard anodised aluminium / Delrin |
| switch type | magnetic switch 3 levels of light intensity discharge warning message backup mode |
| max. length | 117 mm |
| max. diameter | 61 mm |
| front glass | 6mm tempered |
| weight | 340 g |
| weight in water | 130 g |
| max.operation depth | 200 m |